

# the PREMIUM HIGH RATE SERIES

## INTRODUCTION

The POWER HIGH RATE PREMIUM TCXC and SLF are the ideal choice in applications where additional specification features and options and adherence to national standards is required. This range is an ideal choice for exacting UPS, Emergency Lighting and Switchgear applications. The range has a 10 year design life which also comes with all the pedigree, features and design characteristics of the PRC/TC range, providing a compact design ideal for low maintenance and space restricted applications.



†TC6225XC



† SLF-12250



† TC-12150XC

## STANDARD FEATURES ARE AS THE HIGH RATE SERIES

- Ten year life design
- Valve Regulated Lead Acid Battery VRLA
- Flame retardant case and cover compliant to UL 94VO and UL94V2 for SLF Models

## ADDITIONAL FEATURES OF THE HIGH RATE PREMIUM TCXC SERIES

- Copper inserted terminals - Single tool use
- Product Range is compliant with UL924, BS6290 and IEC60896-22
- Flame Retardancy meets UL94VO
- Warranty extension options are available
- Additional SLF versions with Front Terminals

## HIGH RATE PREMIUM SERIES 10 YEAR DESIGN LIFE SPECIFICATIONS

MODEL	VOLTS	CAPACITY TO 1.75 VOLTS PER CELL @ 25°C				DIMENSIONS (MM)			WEIGHT (KG)	TERMINAL AVAILABLE *
		3 HOURS	8 HOURS	10 HOURS	20 HOURS	L	W	H		
TC-1250XC	12	40	45	46	50	219	137	208	16.0	C
TC-1255XC	12	42	47	48	55	229	140	229	19.3	C
TC-1290XC	12	60	68	70	76	259	169	229	26.3	C
TC-12100XC	12	72	82	84	91	305	169	231	30.2	C
TC-12120XC	12	85	96	98	110	343	173	215	35.5	C
TC-12150XC	12	103	128	140	136	343	173	273	47.6	C
TC-6225XC	6	167	193	199	220	272	187	278	37.0	C
SLF-12105	12	72	82	84	91	534	109	245	31.4	C
SLF-12120	12	87	96	99	110	534	109	245	35.2	C
SLF-12205	12	147	170	174	184	536	215	256	65.9	C
SLF-12250	12	180	200	205	220	536	215	256	72.5	C

†Product colour supplied may differ from that shown

\* TERMINAL: C = Copper insert